



Main

Product or component type	Fuse monitor
Electrical circuit type	Electronic
Device application	Signalling
Accessory / separate part category	Electrical accessory

Complementary

Range compatibility	Fupact ISFL ISFL160 fuse-switch disconnecter
Mounting mode	Fixed
Control type	Handle
[Ue] rated operational voltage	400...690 V
[Ie] rated operational current	3 A (AC-15) at 200...240 V AC 3 A (AC-15) at 250 V AC 2 A (DC-13) at 24 V DC
Rated breaking capacity	2 kA
[Ui] rated insulation voltage	250 V
Minimum load	10 mA 24 V
Standards	EN 61000-4-5 EN 61000-4-3 ENV 50204 EN 55022 EN 61000-4-2 EN 61000-4-4 EN 61000-4-6
Product certifications	CE
Net weight	0.2 kg

Environment

IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	322 g
Package 1 Height	5.5 cm
Package 1 width	15 cm
Package 1 Length	44 cm
Unit Type of Package 2	S04
Number of Units in Package 2	11
Package 2 Weight	5.144 kg
Package 2 Height	30 cm

Package 2 width	40 cm
Package 2 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------