



Main

Range of product	ISFL1250 ISFL250...630
Range	FuPact
Product or component type	Current transformer
Device application	Power supply
Range compatibility	Fupact ISFL ISFL250 fuse-switch disconnecter Fupact ISFL ISFL400 Fupact ISFL ISFL630 Fupact ISFL ISFL1250
Current transformer ratio	400/5 A
Power consumption in VA	5 VA

Complementary

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Maximum safety factor	5
[Ue] rated operational voltage	800 V AC 50/60 Hz
IP degree of protection	IP20
Standards	IEC 60044-1 VDE 0414 BS 7626
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Height	78 mm
Width	60 mm
Depth	30 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	163 g
Package 1 Height	4.6 cm
Package 1 width	6.5 cm
Package 1 Length	8 cm
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	6.975 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------