



Main

Range of product	Masterpact NT
Product or component type	Basic frame
Device short name	Masterpact NT06
Circuit breaker name	Masterpact NT06L1
Poles description	4P
Neutral position	Left
Network type	AC
Breaking capacity code	L1
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A

Complementary

Network frequency	50/60 Hz
Control type	Push-button
Mounting mode	Fixed
[In] rated current	630 A at 40 °C
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	220 KA 525 V AC at 50/60 Hz 286 KA 440 V AC at 50/60 Hz 330 KA 220/415 V AC at 50/60 Hz 52 kA 690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	630 A
Breaking capacity	100 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 130 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 25 KA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 150 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 150 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	100 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 130 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 150 KA at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2
Protection type	Without protection
Mechanical durability	12500 cycles without maintenance conforming to IEC 60947-2
Electrical durability	AC-23A: 3000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-3: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 2000 Cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 3000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2
Connection pitch	70 mm
[Icw] rated short-time withstand current	10 kA 0.5 s conforming to IEC 60947-2
Integral instant protection	5.67...6.93 kA
Maximum breaking time	9 ms
Maximum closing response time	50 ms
Height	301 mm
Width	346 mm
Depth	196 mm

Environment

Standards	IEC 60947-2
Product certifications	LCIE ASEFA
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Contractual warranty

Warranty	18 months
----------	-----------