



Main

Range	Masterpact
Product name	Masterpact MTZ2
Device short name	MTZ2 16 H1
Product or component type	Circuit breaker
Device application	Protection
Poles description	4P
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Breaking capacity code	H1
Suitability for isolation	Yes conforming to IEC 60947-2
Selectivity category	Category B

Complementary

Control type	Push-button
Mounting mode	Fixed
Mounting support	Rails Base plate
[In] rated current	1600 A at 40 °C
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	145 KA 220/415 V AC at 50/60 Hz 145 KA 440 V AC at 50/60 Hz 145 KA 500/525 V AC at 50/60 Hz 145 kA 660/690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	1600 A
Performance level	66 KA Icu at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 66 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 66 KA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 66 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	66 KA at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 66 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 66 KA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 66 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical durability	25000 cycles with periodic preventive maintenance conforming to IEC 60947-2
Electrical durability	10000 Cycles 440 V AC 50/60 Hz conforming to IEC 60947-2 10000 Cycles 690 V AC 50/60 Hz conforming to IEC 60947-2 AC-23A: 10000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3 AC-23A: 10000 cycles 690 V AC 50/60 Hz conforming to IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to IEC 60947-3
Connection pitch	115 mm
[Icw] rated short-time withstand current	66 KA 0.5 s conforming to IEC 60947-2 66 KA 1 s conforming to IEC 60947-2 36 kA 3 s conforming to IEC 60947-2
Maximum breaking time	25 ms
Maximum closing response time	70 ms
Height	352 mm
Width	537 mm
Depth	300 mm

Environment

Standards	IEC 60947-2 IEC 60364-8-1
Product certifications	ASTA
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes