

Product data sheet

Characteristics

LV848349

Circuit breaker Masterpact MTZ3 63H2, 6300 A, 3P drawout, without Micrologic



Main

| | |
|---------------------------|-------------------------------|
| Range | Masterpact |
| Product name | Masterpact MTZ3 |
| Device short name | MTZ3 63 H2 |
| Product or component type | Circuit breaker |
| Device application | Protection |
| Poles description | 3P |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Breaking capacity code | H2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Selectivity category | Category B |

Complementary

| | |
|---|---|
| Control type | Push-button |
| Mounting mode | Drawout |
| Mounting support | Base plate Rails |
| [In] rated current | 6300 A at 40 °C |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uiimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |
| [Icm] rated short-circuit making capacity | 330 KA 220/415 V AC at 50/60 Hz 330 KA 440 V AC at 50/60 Hz 286 KA 500/525 V AC at 50/60 Hz 220 kA 660/690 V AC at 50/60 Hz |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 6300 A |
| Performance level | 150 KA Icu at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 150 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 130 KA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 150 KA at 220/415 V AC 50/60 Hz conforming to IEC 60947-2 150 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 130 KA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 10000 cycles with periodic preventive maintenance conforming to IEC 60947-2 |
| Electrical durability | AC-3: 6000 cycles 440/690 V AC 50/60 Hz conforming to IEC 60947-3 1500 Cycles 440 V AC 50/60 Hz conforming to IEC 60947-2 1500 Cycles 690 V AC 50/60 Hz conforming to IEC 60947-2 AC-23A: 1500 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3 AC-23A: 1500 cycles 690 V AC 50/60 Hz conforming to IEC 60947-3 |
| Connection pitch | 230 mm |
| [Icw] rated short-time withstand current | 100 KA 0.5 s conforming to IEC 60947-2 100 KA 1 s conforming to IEC 60947-2 100 kA 3 s conforming to IEC 60947-2 |
| Integral instant protection | 243...297 kA |
| Maximum breaking time | 25 ms |
| Maximum closing response time | 80 ms |
| Height | Drawout circuit breaker without chassis: 300 mm Drawout circuit breaker with chassis: 479 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-------|---|
| Width | Drawout circuit breaker without chassis: 668 mm Drawout circuit breaker with chassis: 786 mm |
| Depth | Drawout circuit breaker without chassis: 300 mm Drawout circuit breaker with chassis: 403 mm |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | IEC 60364-8-1 IEC 60947-2 |
| Product certifications | ASEFA |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| PVC free | Yes |