Product data sheet Characteristics

LV480818

ISFT160 - insulated connector for feeding devices





| Main | |
|------------------------------------|--|
| Product or component type | Connector |
| Accessory / separate part category | Connection accessory |
| Range compatibility | Fupact ISFL ISFL160 fuse-switch disconnector |
| Poles description | 3P |
| Quantity per set | Set of 3 |

Complementary

| [In] rated current | 160 A | |
|-------------------------|--|--|
| Conductor material | Copper | |
| Connections - terminals | Bare cable connectors1 cable(s) 2595 mm² | |
| Tightening torque | 12 N.m | |

Environment

| IP degree of protection | IP2x |
|-------------------------|------|
| | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|---------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Weight | 347 g | |
| Package 1 Height | 2.5 cm | |
| Package 1 width | 11.5 cm | |
| Package 1 Length | 21 cm | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---------------------------------|--|
| REACh Regulation | ☑ REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EEEU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| Environmental Disclosure | ☑ Product Environmental Profile | |
| | | |