

Product data sheet

Characteristics

M9XUPC04

Multi9 - terminals for M9XU comb busbar - set of 4



Main

Range of product	Multi 9
Product or component type	Connector
Accessory / separate part category	Connection accessory
Quantity per set	Set of 4

Complementary

[In] rated current	63 A
[Ui] rated insulation voltage	1000 V
Connection pitch	18 mm
Standards	UL 486E
Product certifications	CURus IEC
Colour	White (RAL 9001)
Connections - terminals	Screw terminal top connector 6...35 mm ² rigid Screw terminal top connector 6...35 mm ² flexible
Tightening torque	3.5 N.m
Range compatibility	Multi 9 C60 C60BP comb busbar

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	150 g
Package 1 Height	3.1 cm
Package 1 width	9.1 cm
Package 1 Length	11.2 cm
Unit Type of Package 2	S02
Number of Units in Package 2	25
Package 2 Weight	4.006 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins