

Product data sheet

Characteristics

33608

front connections, 630 A to 1000 A, fixed
ComPact NS type N/H/NA, top mounting, 4
poles



Main

| | |
|------------------------------------|---|
| Product or component type | Front connection |
| Accessory / separate part category | Connection accessory |
| Range compatibility | ComPact NS630b...1600 circuit breaker ComPact NS630b...1600 switch disconnector |
| Poles description | 4P |
| [In] rated current | 630 A H fixed 800 A H fixed 1000 A H fixed 630 A N fixed 800 A N fixed 1000 A N fixed 630 A NA fixed 800 A NA fixed 1000 A NA fixed |

Complementary

| | |
|------------------------------------|--------------------------------------|
| Location of connection | Front |
| Localisation on device | Upside |
| Connection pitch | 70 mm |
| Accessory / separate part category | Spare part for ComPact NS630b...1600 |

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 1.359 kg |
| Package 1 Height | 2.700 cm |
| Package 1 width | 12.000 cm |
| Package 1 Length | 27.900 cm |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|