

# Product data sheet

## Characteristics

48140

rear connection downside vertical mounting -  
for NW 40 - 3 poles



### Main

Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW40 switch disconnector Masterpact NW Masterpact NW40 circuit breaker
Poles description	3P
[In] rated current	4000 A H1 drawout 4000 A H2 drawout 4000 A H2A drawout 4000 A H10 drawout 4000 A H1b drawout 4000 A H3 drawout 4000 A H1 fixed 4000 A H2 fixed 4000 A H2A fixed 4000 A H1b fixed 4000 A HA drawout 4000 A HF drawout 4000 A HA10 drawout 4000 A HA fixed 4000 A HF fixed 4000 A HA10 fixed

### Complementary

Location of connection	Rear
Localisation on device	Downside
Connection position	Vertical
Connection pitch	115 mm

### Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------