Product data sheet Characteristics

48416

front connection upside mounting - for NW 25..32 cradle - 3 poles



Main	
Product or component type	Front connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW25 switch
	disconnector
	Masterpact NW Masterpact NW32 switch disconnector
	Masterpact NW Masterpact NW32 circuit breaker
	Masterpact NW Masterpact NW25 circuit breaker
Poles description	3P
[In] rated current	3200 A H1 drawout
	3200 A H2 drawout
	3200 A H3 drawout
	2500 A H1 drawout
	2500 A H2 drawout
	2500 A H1b drawout
	2500 A N2 drawout
	2500 A HA drawout
	2500 A HF drawout
	2500 A HA10 drawout
	3200 A H1b drawout
	3200 A HA drawout
	3200 A HF drawout
	3200 A HA10 drawout
	2500 A H3 drawout
	2500 A H10 drawout
	3200 A H10 drawout

Complementary

Location of connection	Front
Localisation on device	Upside
Connection pitch	115 mm

Offer Sustainability

Office Odditalitability	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

14/	40 (1
Warranty	18 months
	10 111011110