



Main

Product or component type	Front connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW08 switch disconnecter Masterpact NW Masterpact NW10 switch disconnecter Masterpact NW Masterpact NW12 switch disconnecter Masterpact NW Masterpact NW16 switch disconnecter Masterpact NW Masterpact NW08 circuit breaker Masterpact NW Masterpact NW16 circuit breaker Masterpact NW Masterpact NW10 circuit breaker Masterpact NW Masterpact NW12 circuit breaker Masterpact NW Masterpact NW02 circuit breaker
Poles description	3P
[In] rated current	800 A H1 drawout 800 A H2 drawout 800 A H3 drawout 800 A L1 drawout 1000 A H1 drawout 1000 A H2 drawout 1000 A H3 drawout 1000 A L1 drawout 1250 A H1 drawout 1250 A H2 drawout 1250 A H3 drawout 1600 A H1 drawout 1600 A H2 drawout 1600 A H3 drawout 800 A N1 drawout 800 A HA drawout 1000 A HA drawout 1250 A HA drawout 1600 A HA drawout 1250 A HF drawout 1600 A N1 drawout 1600 A L1 drawout 800 A H2A drawout 1000 A N1 drawout 1250 A N1 drawout 1250 A L1 drawout 800 A H1b drawout 800 A N2 drawout 800 A HF drawout 800 A HA10 drawout 1000 A H1b drawout 1000 A N2 drawout 1000 A HF drawout 1000 A HA10 drawout 1250 A H1b drawout 1250 A N2 drawout 1250 A HA10 drawout 1600 A H1b drawout 1600 A N2 drawout 1600 A HF drawout 1600 A HA10 drawout 250 A H1 drawout

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Location of connection	Front
Localisation on device	Downside
Connection pitch	115 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.82 kg
Package 1 Height	3 cm
Package 1 width	7.6 cm
Package 1 Length	20 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------