48150

rear connection downside horizontal mounting - for NW 40 - 3 poles



Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW40 switch
	disconnector
	Masterpact NW Masterpact NW40 circuit breaker
Poles description	3P
[In] rated current	4000 A H1 drawout
	4000 A H2 drawout
	4000 A H2A drawout
	4000 A H10 drawout
	4000 A H1b drawout
	4000 A H3 drawout
	4000 A H1 fixed
	4000 A H2 fixed
	4000 A H2A fixed
	4000 A H1b fixed
	4000 A HA drawout
	4000 A HF drawout
	4000 A HA10 drawout
	4000 A HA fixed
	4000 A HF fixed
	4000 A HA10 fixed

Complementary

Location of connection	Rear	
Localisation on device	Downside	
Connection position	Horizontal	
Connection pitch	115 mm	

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

oontractaar warranty		
Warranty	18 months	