

Product data sheet

Characteristics

48160

rear connection upside vertical mounting - for
NW 40 - 4 poles



Main

Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW40 switch disconnector Masterpact NW Masterpact NW40 circuit breaker
Poles description	4P
[In] rated current	4000 A H1 drawout 4000 A H2 drawout 4000 A H2A drawout 4000 A H10 drawout 4000 A H1b drawout 4000 A H3 drawout 4000 A H1 fixed 4000 A H2 fixed 4000 A H2A fixed 4000 A H1b fixed 4000 A HA drawout 4000 A HF drawout 4000 A HA10 drawout 4000 A HA fixed 4000 A HF fixed 4000 A HA10 fixed

Complementary

Location of connection	Rear
Localisation on device	Upside
Connection position	Vertical
Connection pitch	115 mm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------