

Product data sheet

Characteristics

LV432591

short terminal shield, ComPact NSX400/630,
pitch 45 mm, IP40, 3 poles



Main

Product or component type	Short terminal shield
Range compatibility	ComPact NSX400 ComPact NSX630 Compact NSX400 DC Compact NSX630 DC EasyPact CVS400 EasyPact CVS630 PowerPact L
Accessory / separate part type	Insulation accessories
Poles description	3P
Quantity per set	1

Complementary

Connection pitch	45 mm
IP degree of protection	IP40

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	112 g
Package 1 Height	5.1 cm
Package 1 width	11.9 cm
Package 1 Length	21.9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Weight	2.732 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Weight	34.136 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation

 China RoHS Declaration

Environmental Disclosure

 Product Environmental Profile

Contractual warranty

Warranty

18 months
