



Main

Product or component type	Voltage presence indicator
Device application	Monitoring
Range compatibility	ComPact NSX400 ComPact NSX630 Compact INS Compact INV
Poles description	3P 4P
[In] rated current	630 A

Complementary

[Ue] rated operational voltage	220...550 V
Network type	AC
Network frequency	50/60 Hz







Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	101 g
Package 1 Height	8 cm
Package 1 width	9 cm
Package 1 Length	13 cm
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Weight	3.541 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------