



Main

Range	Masterpact
Device short name	K70 K60 K80
Product or component type	Isolating block
Device application	Coil protection
Range compatibility	MX com coil XF com coil

Complementary

Control type	Communicating
Mounting location	Control enclosure
Product destination	Control unit
Localisation on device	Behind control unit
[Uc] control circuit voltage	480 V AC

Environment

Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20 g
Package 1 Height	3 cm
Package 1 width	5 cm
Package 1 Length	6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	16
Package 2 Weight	1.32 kg
Package 2 Height	9 cm
Package 2 width	13 cm
Package 2 Length	18 cm
Unit Type of Package 3	S02
Number of Units in Package 3	96
Package 3 Weight	2.25 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information