



Main

| | |
|--------------------------------|---|
| Range | Masterpact |
| Range of product | Masterpact NT Masterpact NW |
| Product or component type | Control unit |
| Trip unit name | Micrologic 5.0 H |
| Trip unit technology | Electronic |
| Range compatibility | Masterpact NT06...16 Masterpact NW08...40 Masterpact NW40b...63 |
| Device application | Distribution |
| Number of poles | 4P 3P |
| Protected poles description | 4t 3t 3t + N/2 |
| Trip unit protection functions | Selective protection |
| Protection type | For short time short-circuit protection For overload protection (long time) For instantaneous short-circuit protection |
| Trip unit rating | 630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A at 50 °C 2500 A at 50 °C 3200 A at 50 °C 4000 A at 50 °C 5000 A at 50 °C 6300 A at 50 °C |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|--|---|
| Long-time pick-up adjustment type I_r (thermal protection) | Adjustable 9 settings |
| [I_r] long-time protection pick-up adjustment range | 0.4...1 x I_n |
| Long-time protection delay adjustment type t_r | Adjustable 9 settings |
| [t_r] long-time protection delay adjustment range | 0.7...16.6 S at 7.2 x I_r 0.7...24 S at 6 x I_r 12.5...600 s at 1.5 x I_r |
| Thermal memory | 20 mn |
| Short-time protection pick-up adjustment type I_{sd} | Adjustable 9 settings |
| [I_{sd}] Short-time protection pick-up adjustment range | 1.5...10 x I_r |
| Short-time protection delay adjustment type t_{sd} | Adjustable |
| [t_{sd}] Short-time protection delay adjustment range | 0...0.4 S $I^2t=off$ 0.1...0.4 s $I^2t=on$ |
| Instantaneous protection pick-up adjustment type I_i | Adjustable 9 settings |
| [I_i] instantaneous protection pick-up adjustment range | 2...15 x I_n Off |
| Earth-leakage protection | Without |

| | |
|---------------------------------|--|
| Zone selective interlocking ZSI | With |
| Local signalling | 3 LEDs (red) for electrical fault 1 LED (red) for internal error |
| Display type | Digital display |
| Type of measurement | Harmonics meter Power meter |
| Communication of data | Measurement readout Protection and alarm settings Maintenance indicators |

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| REACh Regulation |  REACh Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|