



Main

Range	Masterpact
Range of product	Masterpact NT
Product or component type	Control unit
Trip unit name	Micrologic 5.0 H
Trip unit technology	Electronic
Range compatibility	Masterpact NT06...16
Device application	Distribution
Number of poles	4P 3P
Protected poles description	4t 3t 3t + N/2
Trip unit protection functions	Selective protection
Protection type	For short time short-circuit protection For overload protection (long time) For instantaneous short-circuit protection
Trip unit rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Drawout

Complementary

Long-time pick-up adjustment type $Ir$ (thermal protection)	Adjustable 9 settings
[ $Ir$ ] long-time protection pick-up adjustment range	0.4...1 x $In$
Long-time protection delay adjustment type $tr$	Adjustable 9 settings
[ $tr$ ] long-time protection delay adjustment range	0.7...16.6 S at 7.2 x $Ir$ 0.7...24 S at 6 x $Ir$ 12.5...600 s at 1.5 x $Ir$
Thermal memory	20 mn
Short-time protection pick-up adjustment type $Isd$	Adjustable 9 settings
[ $Isd$ ] Short-time protection pick-up adjustment range	1.5...10 x $Ir$
Short-time protection delay adjustment type $tsd$	Adjustable
[ $tsd$ ] Short-time protection delay adjustment range	0...0.4 S $I^2t=off$ 0.1...0.4 s $I^2t=on$
Instantaneous protection pick-up adjustment type $II$	Adjustable 9 settings
[ $II$ ] instantaneous protection pick-up adjustment range	2...15 x $In$ Off
Earth-leakage protection	Without
Zone selective interlocking ZSI	With
Local signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Display type	Digital display

Type of measurement	Harmonics meter Power meter
Communication of data	Measurement readout Protection and alarm settings Maintenance indicators

## Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------