



Main

| | |
|---|---|
| Range | TeSys |
| Product name | TeSys GB2 |
| Device short name | GB2 |
| Product or component type | Circuit breaker |
| Device application | Control |
| Poles description | 2P |
| Network type | AC/DC |
| Utilisation category | Category A conforming to IEC 60947-2 DC-12 conforming to IEC 60947-5-1 DC-13 conforming to IEC 60947-5-1 |
| Network frequency | 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity | 3 KA Icu at 110 V AC 50/60 Hz conforming to IEC 60947-2 1.5 KA Icu at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 1.5 KA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 1.5 KA Icu at 24 V DC conforming to IEC 60947-2 1 kA Icu at 48 V DC conforming to IEC 60947-2 |
| [Ics] rated service short-circuit breaking capacity | 75 % at 110 V AC 50/60 Hz conforming to IEC 60947-2 75 % at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 75 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 |
| Trip unit technology | Thermal-magnetic |
| Magnetic tripping current | 108 A |

Complementary

| | |
|---|--|
| Mounting mode | By clips |
| Mounting support | Plate Rail |
| Mounting position | Vertical Horizontal |
| Control type | Toggle |
| [In] rated current | 8 A |
| [Ue] rated operational voltage | 415 V AC 50/60 Hz conforming to IEC 60947-2 48 V DC |
| [Uiimp] rated impulse withstand voltage | 4 kV IEC 60947-2 |
| Power dissipation per pole | 2 W |
| Mechanical durability | 8000 cycles |
| Electrical durability | 8000 cycles |
| Connections - terminals | Connector 1 cable(s) 0.75...6 mm ² solid without cable end Connector 2 cable(s) 0.75...4 mm ² solid without cable end Connector 1 cable(s) 0.75...4 mm ² flexible with cable end Connector 2 cable(s) 0.75...2.5 mm ² flexible with cable end |
| Tightening torque | 1.2 N.m on connector |
| Mechanical robustness | Shocks: 22 Gn for 20 ms conforming to IEC 60068-2-27 Vibrations: 5 Gn, 5...110 Hz conforming to IEC 60068-2-6 |
| Quantity per set | Set of 3 |
| 9 mm pitches | 4 |

| | |
|------------|----------|
| Height | 74 mm |
| Width | 30 mm |
| Depth | 70 mm |
| Net weight | 0.115 kg |

Environment

| | |
|---------------------------------------|------------------------------------|
| Standards | EN/IEC 60947-1 EN/IEC 60947-2 |
| Protective treatment | TC |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage | -40...80 °C |
| Fire resistance | 960 °C conforming to IEC 60695-2-1 |
| Operating altitude | 3000 m |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 107 g |
| Package 1 Height | 8.2 cm |
| Package 1 width | 8.5 cm |
| Package 1 Length | 9.7 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 3 |
| Package 2 Weight | 347 g |
| Package 2 Height | 8.2 cm |
| Package 2 width | 8.5 cm |
| Package 2 Length | 9.7 cm |
| Unit Type of Package 3 | S02 |
| Number of Units in Package 3 | 36 |
| Package 3 Weight | 4.469 kg |
| Package 3 Height | 15 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|