

# A9F74250

Miniature circuit-breaker, Acti9 iC60N, 2P, 50 A, C curve, 6000 A (IEC 60898-1), 10 kA (IEC 60947-2)



## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device application        | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Range                     | Acti 9                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Product name              | Acti 9 iC60                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device short name         | IC60N                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Poles description         | 2P                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Number of protected poles | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| [In] rated current        | 50 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Network type              | AC<br>DC                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Curve code                | C                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Breaking capacity         | 6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>36 KA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 KA Icu at ≤ 125 V DC conforming to EN/IEC 60947-2<br>10 KA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>20 KA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>6 KA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>36 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Utilisation category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                          |
| Suitability for isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                       |
| Standards                 | EN 60898-1<br>IEC 60898-1<br>IEC 60947-2<br>EN 60947-2                                                                                                                                                                                                                                                                                                                                                                                                               |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network frequency                                | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Magnetic tripping limit                          | 8 x I <sub>n</sub> +/- 20 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| [Ics] rated service breaking capacity            | 15 KA 75 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 KA 75 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 KA 75 % conforming to EN 60947-2 - 440 V AC 50/60 Hz<br>15 KA 75 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 KA 75 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 KA 75 % conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>27 KA 75 % conforming to IEC 60947-2 - 12...133 V AC 50/60 Hz<br>27 KA 75 % conforming to EN 60947-2 - 12...133 V AC 50/60 Hz<br>6000 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz<br>6000 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz<br>10 KA 100 % conforming to IEC 60947-2 - 72...125 V DC<br>10 kA 100 % conforming to EN 60947-2 - 72...125 V DC |
| [Ui] rated insulation voltage                    | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| [Uimp] rated impulse withstand voltage           | 6 KV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Contact position indicator                       | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Control type                                     | Toggle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Local signalling                                 | Trip indicator                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mounting mode                                    | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mounting support                                 | DIN rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Comb busbar and distribution block compatibility | Top or bottom: YES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 9 mm pitches                                     | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Height                                           | 85 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Width                                            | 36 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Depth                                            | 78.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Net weight                                       | 0.25 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Colour                                           | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mechanical durability                            | 20000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Electrical durability                            | 10000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Connections - terminals                          | Single terminal (top or bottom) 1...35 mm <sup>2</sup> rigid<br>Single terminal (top or bottom) 1...25 mm <sup>2</sup> flexible                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Wire stripping length                            | 14 mm for top or bottom connection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Tightening torque                                | 3.5 N.m top or bottom                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Earth-leakage protection                         | Separate block                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## Environment

|                                       |                                                             |
|---------------------------------------|-------------------------------------------------------------|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP20 conforming to EN 60529 |
| Pollution degree                      | 3 conforming to EN 60947-2<br>3 conforming to IEC 60947-2   |
| Overvoltage category                  | IV                                                          |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                 |
| Relative humidity                     | 95 % at 55 °C                                               |
| Operating altitude                    | 0...2000 m                                                  |
| Ambient air temperature for operation | -35...70 °C                                                 |
| Ambient air temperature for storage   | -40...85 °C                                                 |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Weight             | 253 g  |
| Package 1 Height             | 3.5 cm |
| Package 1 width              | 7 cm   |
| Package 1 Length             | 9.5 cm |
| Unit Type of Package 2       | BB1    |

|                              |           |
|------------------------------|-----------|
| Number of Units in Package 2 | 6         |
| Package 2 Weight             | 1.602 kg  |
| Package 2 Height             | 8 cm      |
| Package 2 width              | 9.7 cm    |
| Package 2 Length             | 22.5 cm   |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 66        |
| Package 3 Weight             | 18.095 kg |
| Package 3 Height             | 30 cm     |
| Package 3 width              | 30 cm     |
| Package 3 Length             | 40 cm     |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|