



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Magnetic TM -DC,
Breaking capacity code	L
Options	Shunt trip 250 V DC Shunt trip 120 V AC

Complementary

[In] rated current	70 A
Number of Poles	3P
Interrupt Rating	At 500 V DC 50 kA at 500 V DC
[Ue] rated operational voltage	250 V DC 500 V DC
Continuous current rating	80 %
Trip Unit	Trip unit
Mounting mode	Unit mount
Electrical connection	Terminal nut load Terminal nut line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Height	162.56 mm
Width	104.65 mm
Depth	110.74 mm

Environment

Product certifications	UL listed CSA CE CCC IEC
Ambient air temperature for operation	40 °C

Packing Units

Package 1 Weight	3.629 kg
------------------	----------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes