



### Main

Range of product	Acti 9
Product name	Acti 9 iCT+
Product or component type	Contacteur
Device short name	ICT+
Device application	Control circuit
Poles	1P
[I <sub>e</sub> ] rated operational current	20 A AC-7A 20 A AC-7B
Pole contact composition	1 NO
Network type	AC
Control type	Remote and manual control
[U <sub>c</sub> ] control circuit voltage	230 V AC 50 Hz

### Complementary

Network frequency	50 Hz
[U <sub>e</sub> ] rated operational voltage	250 V AC 50 Hz
Maximum power	3.6 kW at 250 V AC
[U <sub>i</sub> ] rated insulation voltage	300 V
Control signal type	Maintained
Switching frequency	6 switching operation/minute
Local signalling	Color indicator
Hold-in power consumption in VA	1.1 VA
Inrush power in VA	11 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Net weight	70 g
Colour	White
Mechanical durability	5000000 cycles
Connections - terminals	Tunnel type terminal2 cable(s) 1.5 mm <sup>2</sup> rigid Tunnel type terminal2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule Tunnel type terminal2 cable(s) 2.5 mm <sup>2</sup> rigid Tunnel type terminal2 cable(s) 2.5 mm <sup>2</sup> flexible Tunnel type terminal1 cable(s) 4 mm <sup>2</sup> rigid Tunnel type terminal1 cable(s) 4 mm <sup>2</sup> flexible
Tightening torque	1 N.m
Wire stripping length	10 mm
Product compatibility	No auxiliary
Compatibility code	ICT+
Market segment	Small commercial Residential

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	EN 60669-2-1
Product certifications	NF
Noise level	10 dB
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-40...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	88 g
Package 1 Height	3 cm
Package 1 width	7 cm
Package 1 Length	9.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	773 g
Package 2 Height	8 cm
Package 2 width	9.7 cm
Package 2 Length	26.5 cm
Unit Type of Package 3	S02
Number of Units in Package 3	63
Package 3 Weight	6.034 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts & cables product

## Contractual warranty

Warranty	18 months
----------	-----------